

**MONODUR NYLON 6.6, STANDARD:**

Opening / Open Area %	Mesh Opening		Mesh Count		Thread Diameter		Weight oz/yd2
	Inch	Micron	Inch	CM	Inch	Micron	
2000/58	0.0787	2000	9.7	3.8	0.0248	630	8.8
1900/56	0.0748	1900	9.9	3.9	0.0248	630	8.6
1800/60	0.0709	1800	10.9	4.3	0.0209	530	7.4
1700/58	0.0669	1700	11.4	4.5	0.0209	530	7.1
1600/62	0.0630	1600	12.4	4.9	0.0169	430	5.2
1500/60	0.0591	1500	13.2	5.2	0.0169	430	5.5
1400/59	0.0551	1400	14.0	5.5	0.0169	430	5.8
1320/57	0.0520	1320	14.5	5.7	0.0169	430	5.9
1250/60	0.0492	1250	15.7	6.2	0.0146	370	5.1
1180/58	0.0465	1180	16.3	6.4	0.0146	370	5.2
1120/57	0.0441	1120	17.0	6.7	0.0146	370	5.3
1060/55	0.0417	1060	17.8	7.0	0.0146	370	5.5
1000/58	0.0394	1000	19.3	7.6	0.0124	315	3.8
950/56	0.0374	950	20.1	7.9	0.0124	315	4.0
900/55	0.0354	900	20.8	8.2	0.0124	315	4.1
850/53	0.0335	850	21.8	8.6	0.0124	315	4.3
800/56	0.0315	800	23.9	9.4	0.0106	270	3.3
750/54	0.0295	750	24.9	9.8	0.0106	270	3.4
710/52	0.0280	710	25.9	10.2	0.0106	270	3.5
670/51	0.0264	670	26.9	10.6	0.0106	270	3.9
630/49	0.0248	630	28.2	11.1	0.0106	270	4.0
600/48	0.0236	600	29.2	11.5	0.0106	270	4.1
560/53	0.0220	560	33.0	13.0	0.0083	210	3.0
530/51	0.0209	530	34.3	13.5	0.0083	210	3.1
500/50	0.0197	500	35.6	14.0	0.0083	210	3.2
475/48	0.0187	475	37.3	14.7	0.0083	210	3.5
450/47	0.0177	450	38.6	15.2	0.0083	210	3.6
425/45	0.0167	425	40.1	15.8	0.0083	210	3.7
400/43	0.0157	400	41.7	16.4	0.0083	210	3.8
375/41	0.0148	375	43.4	17.1	0.0083	210	4.0
355/48	0.0140	355	49.3	19.4	0.0063	160	2.5
335/46	0.0132	335	51.3	20.2	0.0063	160	2.6
315/44	0.0124	315	53.3	21.0	0.0063	160	2.8
300/49	0.0118	300	58.9	23.2	0.0051	130	1.9
280/47	0.0110	280	62.0	24.4	0.0051	130	2.0
265/45	0.0104	265	64.3	25.3	0.0051	130	2.1
250/43	0.0098	250	66.8	26.3	0.0051	130	2.2
236/42	0.0093	236	69.3	27.3	0.0051	130	2.2
224/46	0.0088	224	77.2	30.4	0.0041	105	1.7
212/45	0.0083	212	80.0	31.5	0.0041	105	1.8
200/43	0.0079	200	83.3	32.8	0.0041	105	1.9
190/50	0.0075	190	94.0	37.0	0.0031	80	1.5
180/48	0.0071	180	97.8	38.5	0.0031	80	1.6
170/46	0.0067	170	102	40.0	0.0031	80	1.7
160/44	0.0063	160	107	42.0	0.0031	80	1.7
150/43	0.0059	150	110	43.5	0.0031	80	1.7
140/40	0.0055	140	114	45.0	0.0031	80	1.8
132/39	0.0052	132	119	47.0	0.0031	80	1.9
125/37	0.0049	125.0	124	49	0.0031	80	1.9
118/36	0.0046	118.0	130	51	0.0031	80	2.0
112/34	0.0044	112.0	132	52	0.0031	80	2.1
106/34	0.0042	106.0	140	55	0.0030	75	1.8
100/33	0.0039	100.0	142	56	0.0030	75	1.8
95/31	0.0037	95.0	147	58	0.0030	75	1.9
90/30	0.0035	90.0	154	61	0.0030	75	1.9
85/28	0.0033	85.0	157	62	0.0030	75	2.0
80/27	0.0031	80.0	164	65	0.0030	75	2.0
71/37	0.0028	71.0	218	86	0.0018	45	0.9
63/34	0.0025	63.0	236	93	0.0018	45	1.0
56/31	0.0022	56.0	254	100	0.0018	45	1.1
50/31	0.0020	50.0	282	111	0.0016	40	0.8
45/28	0.0018	45.0	300	118	0.0016	40	0.9
42.5/26	0.0017	42.5	310	122	0.0016	40	0.9
37.5/23	0.0015	37.5	328	129	0.0016	40	1.0
35.5/25	0.0014	35.5	363	143	0.0014	35	0.7
33.5/24	0.0013	33.5	373	147	0.0014	35	0.8
31.5/23	0.0012	31.5	386	152	0.0014	35	0.8
30/25	0.0012	30.0	419	165	0.0012	30	0.9